

M-DURA™ CENTRESET BAR & PANTRY FAUCET

- Heavy-duty, quarter turn ceramic disc cartridge with a durable brass shell features internal stops to prevent misalignment, ensuring complete shut-off every time
- Solid cast brass construction
- Vandal-resistant torque screw discourages tampering
- Handles feature hot and cold colour indicators
- Designed to be installed through two 1" minimum diameter holes
- Material: Chrome
- Handle Type: Lever
- Mount Location: Deck Mounted
- Installation Holes: 2
- Overall Height: 9-1/2"
- No. of Handles: 2
- Flow Rate: 1.2 GPM
- Connection Type: 1/2" IPS



MOEN®

Model No.	Mfg. No.	Installation Holes	Overall Height"	Aerator Height"	Spout Reach"	Price /Each
PUM086	8270	2	9-1/2	6.25	3-5/8	
PUM088	8279	2	9-1/2	6.25	5-1/4	

M-DURA™ KITCHEN FAUCET

- 1255° Duralast® ceramic cartridge designed to offer the smooth feel and reliable operation of a new faucet from the first time you use it to the last
- Solid cast brass construction
- Vandal-resistant hex screw discourages tampering
- Pull-on/push-off handle
- Designed to be installed through one or three 1-3/8" minimum diameter holes
- Type: Traditional
- Material: Chrome
- Mount Location: Deck Mounted
- No. of Handles: 1
- Handle Type: Lever
- Flow Rate: 1.5 GPM
- Connection Type: 3/8" Compression x 24" Braided Polymer Supply Lines
- Certifications: CSA B125.1
- Manufacturer's Warranty: 5 Year Limited



MOEN®

Model No.	Mfg. No.	Installation Holes	Overall Height"	Aerator Height"	Spout Reach"	Price /Each
PUM093	8701	Multiple	5-1/2	5	9	

M-POWER™ ELECTRONIC FLUSH VALVE

- Sensor-activated, exposed water closet flushometer with brass angle stop valve
- Chloramine resistant seals
- AccuSet™ piston technology delivers virtually maintenance-free precise flush volume, with a stainless steel self-cleaning filter to protect against clogs or damage
- Mechanical override
- Intended for use with floor mounted or wall hung top spud bowls with matching flow rates as specified by the fixture manufacturer
- Toilet flush valves: Adjustable infrared sensor range from 17" to 36"
- Urinal flush valves: Adjustable infrared sensor range up to 15"
- Battery-powered models include 4 AA alkaline batteries
- AC connection models requires 12 V transformer (sold separately)
- Finish: Chrome
- Operating Pressure Range: 15 - 120 PSI
- Manufacturer's Warranty: 5 Year Limited



MOEN®

Model No.	Mfg. No.	Description	Stop Inlet Connection"	Top Spud"	GPF	Price /Each
BATTERY-POWERED						
PUM120	8310	Toilet Flush Valve	1" IPS	1-1/2	1.6	
PUM122	8312	Urinal Flush Valve	3/4" IPS	3/4	1	
AC CONNECTION						
PUM121	8310AC16	Toilet Flush Valve	1" IPS	1-1/2	1.6	
PUM123	8312AC10	Urinal Flush Valve	3/4" IPS	3/4	1	

M-DURA™ CENTRESET KITCHEN FAUCET

- Heavy-duty, quarter turn ceramic disc cartridge with a durable brass shell features internal stops to prevent misalignment, ensuring complete shut-off every time
- Solid cast brass construction
- Vandal-resistant torque screw discourages tampering
- Handles feature hot and cold colour indicators
- Designed to be installed through two or three 1" minimum diameter holes, 8" centreset
- Type: Traditional
- Material: Chrome
- Mount Location: Deck Mounted
- Overall Height: 12"
- No. of Handles: 2
- Handle Type: Lever
- Flow Rate: 1.5 GPM
- Connection Type: 1/2" IPS
- Certifications: CSA B125.1
- Manufacturer's Warranty: 5 Year Limited




MOEN®

Model No.	Mfg. No.	Installation Holes	Overall Height"	Aerator Height"	Spout Reach"	Price /Each
PUM089	8282	Multiple	9-3/4	7.2	9-1/2	
PUM090	8283	Multiple	9-3/4	7.2	9-1/2	
PUM091	8287	Multiple	12	7.2	8	
PUM092	8289	Multiple	12	7.2	8-1/2	

M-DURA™ WALL-MOUNTED SERVICE SINK FAUCET

- Heavy-duty, quarter turn ceramic disc cartridge with a durable brass shell features internal stops to prevent misalignment, ensuring complete shut-off every time
- Solid cast brass construction
- Vandal-resistant torque screw discourages tampering
- Handles feature hot and cold colour indicators
- Includes wall-mounting bracket
- Convenient pail hook
- Material: Chrome
- Type: Traditional
- Handle Type: Lever
- No. of Handles: 2
- Connection Type: 1/2" Eccentric IPS
- Finish: Rough Chrome



MOEN®

Model No.	Mfg. No.	Spout Type	Overall Height"	Aerator Height"	Spout Reach"	Price /Each
PUM094	8230	3/4" Garden Hose Thread	9-1/2	0.01	5-7/8	
PUM095	8124	Vacuum-Breaker Garden Hose Thread	14	0.01	5-7/8	

M-PRESS™ METERING LAVATORY FAUCET

- Pressure-independent design features sealed silicone timing mechanism
- Vandal-resistant hex screw discourages tampering
- Solid brass construction
- Designed to be installed through two 1" minimum diameter holes, 4" centreset
- Single hole mount designed to deliver either tempered or ambient water
- Cycle time easily adjusted from 5 to 60 seconds, independent from water pressure
- Factory preset to automatically shut off after 10 seconds
- Material: Chrome
- Supply Line Pressure Range: 20 - 125 PSI
- Flow Rate: 0.5 GPM
- Connection Type: 1/2" IPS
- Manufacturer's Warranty: 5 Year Limited
- Certifications: CSA B125.1



MOEN®

Model No.	Mfg. No.	No. of Handles	Installation Holes	Overall Height"	Aerator Height"	Price /Each
PUM097	8886	2	2	3-1/2	2.8	
PUM098	8894	1	1	3-3/4	2	
PUM100	99551		4" Commercial Deck Plate for PUM098			