

MOVING SUPPLIES & TIE DOWNS

SAF-T-LOK BARS

- Designed for economy and ease of operation
- Constructed with high strength industrial round tubing
- Easy to close and lock with its heavy-duty steel rack, handle and cast aluminum housing
- Replaceable molded pivoting rubber feet, 2" x 4" that grip firmly to trailer walls
- Easy to open trigger release
- Adjusts from 90" to 105"
- Optional cargo hoop set, two hoops, which bolts quickly and easily to provide greater area of holding surfaces (installation hardware included)
- Available in either steel or aluminum versions
- Extra long steel version is available upon request





KINEDYNE[®]

The Cargo Control People!"

Model	Mfg.		Wt.	Price
No.	No.	Description	lbs.	/Each
ND698	10085	Steel Saf-T-Lok Bar	11.4	
KH574	10088	Aluminum Saf-T-Lok Bar	8.5	
KH575	10096	Cargo Hoop Set 13.3		

KH574

KINEDYNE[®] The Cargo Control People!

JACK BARS

· Designed to hold securely in place

Replaceable molded pivoting 4" x 4"

Adjusts from 86" to 114"

Galvanized finish

rubber feet, that grip firmly to trailer walls

Constructed with high strength industrial square tubing

Patented quick-release handle assembly which allows the

Durable jacking mechanism that securely hold the bar in place

operator to quickly adjust the length of the bar



LOGISTIC TRACKS

SERIES E TRACK HORIZONTAL

- Material: High strength 12-gauge steel
- Minimum Yield: 50 000 PSI
- Finished: Galvanized Weight: 16.2 lb.
- Length: 10 ft.

Model No. ND359 Mfg. No. 43001





Warning:

Price/Each \$

Welding galvanized material may form toxic fumes.

Welding should be done with adequate ventilation.

ROPE TIE-OFFS

- Made with 2" wide 4900G webbing and include 1-27 D-Ring hardware
- Are tagged to comply with North America Cargo Securement Standards
- Working Load Limit: 1,000 lbs.
- Fitting Length: 6"

Model No. PG110 Mfg. No. 660001 Price/Each \$





CORNER PROTECTORS Designed to protect both straps and cargo from damage caused by the load Steel protectors feature a corner recess to protect cargo edges Material: Steel Length: 5" Width: 5' Model No. PG096 Mfg. No. 1863 Price/Each \$ Model No. PG097 PG097 Mfg. No. 1865 Price/Each \$ KINEDYNE The Cargo Control *People!*

ALUMINUM DECKING/SHORING BEAMS

- · For 96" and 102" trailers
- Made from extruded high strength aluminum
- Designed to give maximum strength at the least possible weight
- Keyhole slot allows the beams to be hung and stored in the trailer out of the way when they are not in use
- Decking/Vertical Rating: 2200 lbs. uniformly distributed working load limit
- Head assemblies are all steel, zinc-plated and tapered for ease of operation
- Shoring/Horizontal Rating: 2000 lbs. uniformly distributed working load limit

Note: Working load limits are 1/3 of the ultimate breaking strength.

Model No. ND360 Mfg. No. FE8066-3 Price/Each \$





PE108

CHAINS

Kinedyne® allows consumers to buy chain pre-cut and assembled with grab hook in an "Easy to Carry - Easy to Store Box'

- All Chain is Transportation Grade 70
- Precut to either 16, 20 or 25 foot lengths
- Comes fully assembled with installed grab hooks
- Gold dichromate finish
- All markings & ratings are compliant with the National Association of Chain Manufacturers (NACM)



KINEDYNE The Cargo Control *People!*

Model	Mfg. No.		Chain	Working Load Limit		Price
No.		Length'	Size"	lbs.	kg	/Each
PE963	10034-16BX	16	5/16	4700	2135	
PE964	10034-20BX	20	5/16	4700	2135	
PE965	10034-25BX	25	5/16	4700	2135	
PE966	10038-16BX	16	3/8	6600	3000	
PE967	10038-20BX	20	3/8	6600	3000	
PF968	10038-25RX	25	3/8	6600	3000	