

LADDERS & SCAFFOLDING

COMPLETE 18' DRYWALL BAKER SCAFFOLD TOWER SET

- Overall Height: 236"
- Overall Depth: 122"
- Width: 74"
- Weight: 629.6 lbs.
- Standard(s) Met: ANSI, CSA, OSHA
- Load Capacity: 851 lbs. (387 kg)
Combined Weight of User & Material
- Working Heights: 2.25' - 16.9'
- Reach: 24"
- Caster Size: 5"
- Includes: (3) MetalTech 6' Baker Style Scaffold, (4) 46" Outriggers, (1) Guardrails System, (12) 5" Heavy-Duty Casters

Model No. MP933
Mfg. No. I-T3CISC
Price/Each \$



COMPLETE 12' DRYWALL BAKER SCAFFOLD TOWER SET

- Overall Height: 183"
- Overall Depth: 58-1/2"
- Width: 74"
- Weight: 347.8 lbs.
- Load Capacity: 948 lbs. (431 kg)
Combined Weight of User & Material
- Working Heights: 2.25' - 11.5'
- Reach: 17.5"
- Caster Size: 5"
- Standard(s) Met: ANSI, CSA, OSHA
- Includes: (2) MetalTech 6' Baker Style Scaffold, (4) Outriggers, (1) Guardrails System, (8) 5" Heavy-Duty Casters

Model No. MP934
Mfg. No. I-TCISC
Price/Each \$



JOBSITE SERIES GUARDRAIL SCAFFOLD KIT

- Overall Height: 44-1/2"
- Overall Depth: 29-1/4"
- Width: 69.75"
- Weight: 55.4 lbs.
- Standard(s) Met: ANSI, CSA, OSHA
- Includes: (2) Guardrails with Gates, (4) Toggle Pins

Model No. MP931
Mfg. No. I-CISGRJP
Price/Each \$



COMPLETE MOTORIZED BUILDMAN™ 6' BAKER SCAFFOLD KIT

- The Climb-N-Go was designed to increase worker efficiency, eliminating the need to get off the scaffold to move it
- Equipped with a powerful electric motor, it is propelled by the energy of an 18 to 21 volt battery from any one of the six largest brands in the industry
- Its wheels are installed on the bottom of the scaffolding and the joystick control on the guardrail or directly on a rung
- Compatible with all Metaltech Baker types scaffolding
- Can be powered by: DEWALT®, MAKITA®, MILWAUKEE®, STANLEY® (18V), PORTER CABLE®, BLACK & DECKER®
- Features 4500 feet of battery life on a single battery charge
- Automatic wheel lock safety system
- Moves on a job site without the need for a freight elevator, unlike a scissor lift
- 76" W x 31" D x 118-3/4" H
- Weight: 274.26 lbs.
- Standard(s) Met: CSA S269.2-16, OSHA standards 1926.452(W)
- Includes: (1) Buildman™ 6' Drywall Baker (I-BMSS), (1) Guardrails System (I-BMSGRP), (1) Climb-N-Go (I-CNG)
- Hauling Capacity: 500 lbs. (226.8 kg)

Model No. MP932
Mfg. No. I-CNGBMK
Price/Each \$



PORTABLE ALU SERIES™ SCAFFOLD

- Frame Material: Aluminum
- Overall Height: 72"
- Overall Depth: 29"
- Width: 56.5"
- Weight: 60 lbs.
- Load Capacity: 700 lbs. (318 kg) Combined Weight of User & Material
- Working Heights: 11.75", 23.5", 35.25", 47", 59", 70.75" (30, 60, 90, 119, 150, 180 cm)
- Reach: 12"
- Outside Diameter: 1.5"
- Caster Size: 5"
- Standard(s) Met: ANSI, CSA, OSHA

Model No. MP930
Mfg. No. I-CAIRC
Price/Each \$



BUILDMAN™ PORTABLE SCAFFOLD

- Convenient fold-away tool shelf
- Safety rail to hold onto for stability
- Folds flat for compact storage and transport
- Load Capacity: 750 lbs. (340 kg) Combined Weight of User & Material, 450 lbs. (204 kg) per Platform
- Overall Height: 4'
- Overall Depth: 40-5/8"
- Assembled Dimensions: 50-1/2" x 23-3/4" x 61-1/2" (128.3 x 60.3 x 156.2 cm)
- Weight: 69 lbs.
- Working Heights: 10" - 21-1/2" - 33" (25.4 cm - 54.61 cm - 83.82 cm)
- Platforms: 2 Platforms of 40-5/8" x 8-3/4" x 1-3/4" (103.2 x 22.2 x 4.4 cm)

Model No. MP908
Mfg. No. I-BM4S
Price/Each \$



BUILDMAN™ BAKER DRYWALL SCAFFOLD

- Safeclimb trapdoor and anti-slip deck
- Each end can be adjusted separately to be used on uneven surfaces and stairways
- Safeclimb rung step
- Quick and easy height adjustment
- Overall Height: 6'
- Overall Depth: 31"
- Assembled Dimensions: 75-3/4" x 31" x 76" (192.4 x 78.7 x 193 cm)
- Weight: 165 lbs. (74.8 kg)
- Working Heights: Adjustable from 29" to 71-1/2" (73.7 to 181.6 cm) in 2" (5 cm) increments

Model No. MP909
Mfg. No. I-BMSS
Price/Each \$



SMARTSTAIRS™ MODULAR CONSTRUCTION STAIR SYSTEM

- Solid, non-slip, stable and equipped with robust railings
- Telescopic and modular, Smartstairs™ adapt easily to all types of sites for both indoor and outdoor use
- Revolutionary system to avoid recurring expenses of single-use stairs and their limited lifespan
- The aluminum structure is thick, light, easy to maintain and does not rust
- Easy and quick installation, in less than 30 minutes (no tools are required)
- Ideal for use in industrial, commercial, and residential construction sites
- Material: Aluminium
- Standard(s) Met: OSHA, COHSR

MP920



Model No.	Mfg. No.	Steps	Platform Height"	Min. Platform Height"	Weight lbs.	Price /Each
MP920	AL-SSEH10	6-10	75	45	222.5	
MP921	AL-SSEH16	11-16	120	82-1/2	344.3	
MP922	AL-SSEH21	17-21	157-1/2	127-1/2	443.2	